S9410 Series
Alto Exterior

DIMENSIONS



W	H	D	MC	BASE MODEL NO.
6″	21″	4″	10.5″	**S9410-L12**
6″	21″	4″	10.5″	**S9410-L16**
6″	27″	4″	13.5″	**S9411-L16**
6″	27″	4″	13.5″	**S9411-L20**

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

- Opal Matte Acrylic Lens
- Solid Aluminum Material
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+	Lamp Code	+	CCT	+	Finish	+	Option Code
S9410-L12	+	27K	+	PT	+	Option		
S9410-L16		30K		SD				
S9411-L16		35K		XT				
S9411-L20		40K		CC				

FINISHES

PT Powder Coated Finishes*
SD Shimmer Dimensional Metallic Finishes*
XT Trending Brushed Metal Finishes*
CC Custom Painted Finish
*(Specify Color Code from the list of Finishes [except interior only metallics] – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
EML Remote 10W Emergency LED Battery Backup

LIGHT OUTPUT

LXX = ~ 85 LPW Delivered Lumens (Example: L16= 16W x 85LPW = 1,360 Lumens)

www.ScottArchLighting.com | Tel (707) 864-2172 | Fax (707) 864-2182
© Copyright 2026 Scott Architectural Lighting. All Rights Reserved. Made in the USA.