








# **DIMENSIONS**



Н	W	D	MC	BASE MODEL NO.
22"	6"	5 1/4"	11"	S9475-L12
28"	6"	5 1/4"	14"	S9476-L16

### **SPECIFICATIONS**

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

### **FEATURES**

- Opal Matte Acrylic Lens
- Solid Aluminum Material
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

# ORDER AS A COMPLETE UNIT:

Model No. + Lam	p Code	+ CCT	+ Finis	h + Op	tion C	ode
S9475-L12 S9476-L16	+	27K 30K 35K 40K	+	PT CC BA NT GT CT ZT	+	Option

#### **FINISHES**

BA Brushed Aluminum
PC Polished Chrome
NT Nickel Touch
GT Gold Touch

CT Copper Touch
ZT Bronze Touch
CC Custom Painted Finish
PT Powder Coated Finishes\*

\*(Specify Color Code from the list of Powder Coating Finishes)

## **OPTIONS**

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

\*\* Try our new **Shimmer Metalic Paints**, Formulated for Exterior Conditions.





