


SM060 Series

Spegla

Illuminated Mirrors



FEATURES

- No Illuminated Bands
- Shallow 2-1/8" Depth
- Up to 48" x 96" Max Dimensions
- Perimeter Ambient Light Only

PART NUMBER

SM060_ - _ X _ - L930K - _

For Custom Dimensions, Consult Factory

Note: Dimension cannot exceed 48" x 96". Minimum Width of 24".



Spegla Mirror

SM060 = Glass



Height (in.)

30"
36"
40"



Width (in.)

24"
30"
36"
40"
48"
54"



Source

L930K (Standard)
Options:
L927K
L935K
L940K



Options

NL = Night Light (Separate Circuit)
NS = Night Light w/ Touch Switch
SD = Step Dimming via Touch Switch (Requires Live Circuit)
BAC = Buy America; Buy American Act; and Build America, Buy America Act Compliant.
For other options, consult factory.

SPECIFICATIONS

Housing: Post Powder Coated Heavy Ga. Paintlok™ Steel Housing for structural integrity, Aluminum LED bracketry for heat sinking

LED: 3000K, 90CRI, Constant Voltage. ~7W per linear foot of mirror perimeter.

Driver: Constant voltage 0-10V dimming driver, 120/277V. (Consult factory for other options.)

Mirror: 5MM glass w/polished edges.

Side Lens: Extruded Opal Acrylic

Wiring: Hardwired connection for centrally located J-Box (by others).